Printed Pages: 4



EEC602

(Following Paper ID and Roll No. to be filled in your Answer Book)

PAPER ID : 131602

Roll No.

B. Tech.

(SEM. VI) THEORY EXAMINATION, 2014-15 DIGITAL SIGNAL PROCESSING

Time: 3Hours]

[Total Marks: 100

1 Attempt any four parts

5×4=20

(a) Draw the block diagram for the following system with input x(n) and output y(n)

$$w(n) = x(n) + \frac{1}{2}x(n-1)$$
 and

$$y(n) + \frac{1}{4} y(n-1) = w(n)$$

(b) Obtain the cascade realization for the following system;

$$H(z) = \frac{(1 + \frac{3}{2}z^{-1} + \frac{1}{2}z^{-2})(1 - \frac{3}{2}z^{-1} + z^{-2})}{(1 + z^{-1} + \frac{1}{4}z^{-2})(1 + \frac{1}{4}z^{-1} + \frac{1}{2}z^{-2})}$$

- (c) Calculate the DFT of the sequence $s(n)=\{2,4,2,3\}.$
- (d) State and prove circular convolution property of DFT.
- (e) Explain frequency transformation with LPF to HPF conversion formula.
- (f) Draw a transformation matrix of size 5×5 and explain the properties of twiddle factor.
- 2 Attempt any four parts

5×4=20

(a) Determine H(z) using the impulse invariant technique for the analog system function

$$H(s) = \frac{1}{(s+0.5)(s^2+0.5s+2)}$$

- (b) Realise an FIR filter whose impulse response is h(n)={1, 2, 5, 6, 3, 6, 5, 2, 1} using minimum number of multipliers.
- (c) Determine the response of a discrete-time system for an input signal $s(n)=\{2,1,3,1\}$, if the unit-sample response is of the system is $h(n)=\{1,2,2,-1\}$
- (d) Enumerate and explain the properties of DFT.
- (e) Draw the parallel form network structure of the system with transfer function.

$$H(z) = \frac{2z(z+3)}{z^2 + 0.3z + 0.02}$$

(f) What are the different window functions used for windowing? Explain the effects of using different window functions for designing FIR filter on the filter response. 3 Attempt any two parts

 $10 \times 2 = 20$

- (a) Derive and draw the flow graph for DIF FFT algorithm for N=8.
- (b) Calculate the circular convolution of $s_1(n) = \{1,2,1,2\}$ and $s_2(n) = \{1,2,3,4\}$ using Stockham's method.
- (c) Determine H(z) for a butterworth filter satisfying the following constraints

$$\sqrt{0.5} \le \frac{|H(e^{j\omega})| \le 1}{|H(e^{j\omega})| \le 0.2} \quad \frac{0 \le \omega \le \frac{\pi}{2}}{4} \le \omega \le \pi$$

with T=1 sec. Apply impulse invariant transformation
10×2=20

- 4 Attempt any two parts; 10×2

 (a) Given x(n) =2ⁿ and N=8 find X(K) using DIT

 FFT algorithm. Also calculate the computational
 - reduction factor.

 (b) Design a low-pass filter with the following desired frequency response

$$H_d(e^{j\omega}) = \begin{cases} e^{-j2\omega}, & \frac{-\pi}{4} \le \omega \le \frac{\pi}{4} \\ 0, & \frac{\pi}{4} < |\omega| < \pi \end{cases}$$

and using window function

$$w(n) = \begin{cases} 1, & 0 \le n \le 4 \\ 0, & otherwise \end{cases}$$

(c) Draw the Ladder structure for the system with system function

$$H(z) = \frac{5z^{-3} + 2z^{-2} + 3z^{-1} + 1}{z^{-3} + z^{-2} + z^{-1} + 1}$$

5 Attempt any two parts:

10×2=20

(a) Design a digital chebyshev filter to satisfy the constraints

$$0.77 \le |H(e^{j\omega})| \le 1 \qquad 0 \le \omega \le 0.2\pi$$
$$|H(e^{j\omega})| \le 0.1 \qquad 0.5\pi \le \omega \le \pi$$

Using bilinear transformation with T=1s

(b) Convert the analog filter with system function

$$H(s) = \frac{s+0.1}{(s+0.1)^2+9}$$
 into digital filter with a

resonant frequency of $\omega_r = \frac{\pi}{4}$ of using bilinear transformation.

- (c) Explain the following phenomenon's:
 - (i) Gibbs Oscillations.
 - (ii) Frequency Wraping.